ACP-4340

4U Rackmount Chassis for Full-size SHB/SBC or ATX/MicroATX Motherboard with 4 Hot Swap Drive Trays



Features

- Supports a PICMG backplane with up to 14 slots or an ATX/Micro-ATX motherboard
- Shock-resistant disk drive bay holds four hot-swap 3.5" and 2.5" SATA disk trays, one slim optical disk drive, and one 2.5" internal drive
- Dual front USB 3.0 ports
- Front-accessible system fan without opening top cover for easy maintenance
- LED indicators and alarm notification for system fault detection
- Smart fan speed control
- Built-in Intrusion switch function
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

Quiet Specifications

Drive Bay		External	Internal	
	Slim Optical Drive Bay	1	-	
	3.5"	-	-	
	2.5"	-	1	
	Hot Swap	4 (Compatible with 3.5" or 2.5" devices)	-	
Cooling	Fan	1 (12 cm /74 CFM) + 1 (8 cm/56 CFM) for SATA storage u	nit	
	Air Filter	Yes		
Front I/O Interface	USB 3.0*	2		
Miscellaneous	LED Indicators	Power, HDD, temperature, fan, LAN1, and LAN2		
	Rear Panel	Backplane version: One 9-pin D-Sub opening		
	near ranei	Motherboard version: Five 9-pin D-Sub and one 25-pin D-	Sub openings	
System Monitoring		Chassis intrusion switch		
Intelligent System Module Remote Monitoring	CPU/System fan speed, CPU/system temperature, motherboard voltage (Only selected Advantech MBs/CPU cards with WISE-PaaS/RMM installed can fully enable these functions, check with Advantech local rep. for detailed			
	(only selected Advancen Mbs/or o calos with Wist-rads/minin installed can biny enable these functions, check with Advancen focal rep. for detailed information.)			
Environment		Operating	Non-Operating	
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)	
	Humidity	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing	
	Vibration (5 ~ 500 Hz)	1 Grms	2 G	
	Shock	10 G (with 11 ms duration, half sine wave)		
Physical Characteristics	Dimensions (W x H x D)	482 x 177 x 479 mm (19" x 7.0" x 18.8")		
	Weight	12.5 kg (27.5 lb)		

C € FCC

The USB 3.0 ports do not operate if the motherboard has no on-board USB 3.0 box header.

Front View






LED indicators Slim optical drive bay

Hot-swap HDD tray x4

Front-accessible fan without opening top cover


Rear View






All product specifications are subject to change without notice.

Inside View



ACP-4340



Ordering Information

Part Number	Power Supply	Wattage	Switch type			
Backplane Version						
ACP-4340BP-40ZE	PS8-400ATX-ZE	400W	ATX			
ACP-4340BP-50ZE	PS8-500ATX-ZE	500W	ATX			
ACP-4340BP-70ZE	PS8-700ATX-ZE	700W	ATX			
ACP-4340BP-50RE	RPS8-500ATX-XE	500W (1+1 Redundant)	ATX			
Mother board Version						
ACP-4340MB-40ZE	PS8-400ATX-ZE	400W	ATX			
ACP-4340MB-50ZE	PS8-500ATX-ZE	500W	ATX			
ACP-4340MB-70ZE	PS8-700ATX-ZE	700W	ATX			
ACP-4340MB-50RE	RPS8-500ATX-XE	500W (1+1 Redundant)	ATX			

Optional Accessories

Part Number	Description	
96CB-SATAPOWER-6P2	SATA power wire 6-pin to big 4-pin (for slim ODD)	
98R1434000E	ACP-4340 fan kit for multi GPU card	

Spare Parts

Part Number	Description
9662132020E	Black mobile HDD tray
1990021256T000	Door filter