



**±48V DC Input Industrial PC ATX 12V 2.03
1U Switching Mode Power Supply**

<u>Series</u>	<u>Model No.</u>	<u>Output Watts</u>	<u>Input Voltage</u>	<u>Input Voltage range</u>	<u>Polarity reverse protection</u>
48	STC-48750I	750W continuous	±48V DC	±36V ~ ±70V DC	Protected (Max.100V DC)
	STC-48600I	600W continuous			
	STC-48450I	450W continuous			

* H version (Black color chassis)

ENVIRONMENTAL CONDITIONS:

- ▶ Cooling: Forced Air-cooling, 40x40x28mm Fan x 2 (With Two Ball Bearing)
- ▶ Fan Noise Level: 65dBA @ Full Load (**STC-48450I**)
- ▶ Fan brand: DELTA, NMB, SUNON, SUNON IP68 (for H version) with the same specification
- ▶ Operating Temp.: 0°C~+50°C Full Load
- ▶ Operating Temp.: / **H version** -20°C~+60°C Full Load
- ▶ Operating Humidity: 20%~85% RH Non condensing
- ▶ Operating Humidity: / **H version** 95% RH Non condensing
- ▶ Storage Temperature: -20°C~+80°C
- ▶ Storage Humidity: 10%~90% RH. (Non condensing)
- ▶ Operating Altitude: 10M Below Sea level to Above Sea level 3000M

DC INPUT CHARACTERISTICS:

- ▶ Input connector type 40A/ 300V Single table type Terminal x 2
- ▶ Input Current 12.8A/25A(**750W**) 10.4A/20.8A(**600W**) 8A/16.25A(**450W**)
@Full Load High Line & Low Line
- ▶ Inrush Current Less than 15A Cold start @25°C ambient

DC OUTPUT CHARACTERISTICS:

Output Voltage	Regulation			Output Current						Ripple & Noise
	Load	Line	Cross	750W		600W		450W		
				Min	Max	Min	Max	Min	Max	
+5V	±5%	±1%	±5%	0.5A	35A	0.5A	25A	0A	40A	50mV
+12V				1A	48A	1A	48A	0A	30A	120mV
+3.3V				0.5A	22A	0.5A	22A	0A	22A	50mV
-12V	±8%			0A	0.3A	0A	0.3A	0A	0.3A	120mV
+5VSB	±5%			0.1A	2.5A	0.1A	2.5A	0A	2.5A	50mV
Maximum continuous combined load on +3.3 V & +5V DC output shall not exceed				200		166		166		Wattage
Maximum continuous combined load on +3.3 V & +5V & 12V DC output shall not exceed				720		570		420		
Maximum continuous total DC output power shall not exceed				750		600		450		

OVERALL PERFORMANCE:

- Efficiency 70~75% typical @48V DC Input Full Load
- Hold up time
- Rise time
- Power Good Signal TTL Compatible signal, on delay 100~500ms, off delay 1ms min.
- Short Circuit Protection (SCP) All output equipped with SCP (shutdown and latch off)
- Over Power Protection (OPP) Peak power protected to 130%±10% of continuous rated power (shutdown and latch off)
- Over Voltage Protection (OVP) +3,3V@4.5V, +5V@6V, +12V@15.6V

RELIABILITY:

- MTBF: 80,000 hours @max. Load, 48V DC & 25°C ambient
- Safety Standards: Meet IEC60950-1 and EN60950-1
- Safety Approved:
- EMI Compatibility (EMC): EN55032:2015/AC:2016, CISPR32:2015, EN61000-3-2:2014, EN61000-3-3:2013, EN55024:2010 +A1:2015

ISOLATION:

- INPUT and OUTPUT are isolated by transformers and optical couplers
- Dielectric Withstand INPUT to OUTPUT: 1500V DC for 60 seconds
- Dielectric Withstand INPUT to FRAME GROUND: 1500V DC for 60 seconds
- Leakage Current <0.005μA @48V DC

Output Device Connector Specific:

- ATX 24 Pins x 1 Molex 29-01-2240 or equivalent
- +12V(P4) 4 Pins x 1 Molex 39-01-2040 or equivalent
- HDD, DVD 4 Pins x 7 Molex 8981-04P or equivalent
- FDD 4 Pins x 1 AMP 171822-4 or equivalent
- Serial ATA x 2 Molex 675820000 or equivalent
- CPU EPS 8 Pins x 1 Molex 39-01-2080 or equivalent
- PCIe 12V 6+2 pin x 4

Standard Output Cable Length From Chassis:

550 mm ±50mm / 21.6 inches

PCB specific:

- Layers: 2 / STC-48450I

	6 / STC-48600I , / STC-48750I
▶ Copper:	3 Oz
▶ Thickness:	1.6mm
▶ Material:	FR4
▶ PCB material origin:	Taiwan

Power Chassis Dimension:

205(L) x 100(W) x40.5(H) mm / 8.07(L) x 3.94(W) x 1.59(H) inches / **STC-48450I**
220(L) x 100(W) x40.5(H) mm / 8.66(L) x 3.94(W) x 1.59(H) inches / **STC-48450I (optional)**
240(L) x 100(W) x40.5(H) mm / 9.44(L) x 3.94(W) x 1.59(H) inches / **STC-48600I**
300(L) x 100(W) x40.5(H) mm / 11.81(L) x 3.94(W) x 1.59(H) inches / **STC-48750I**

Net Weight:

2 kg / 4.41 Lbs / **STC-48450I**
2.2 kg / 4.85 Lbs / **STC-48600I**
2.8 kg / 5.95 Lbs / **STC-48750I**

Gross Weight:

2.1~2.4 kg / 4.63 ~ 5.29 Lbs

Packing Detail:

8PCs N.W.: 16 kg / 35.27 Lbs G.W.: 18 kg / 39.68 Lbs / **STC-48450I**
8PCs N.W.: 17.6 kg / 38.8 Lbs G.W.: 20 kg / 44.09 Lbs / **STC-48600I**

Measurement of Carton:

0.049 m³ / 1.73 Cuft