



Key Features

- 15" Intel Core i7/i5 Fanless Stainless Panel PC
- IP66 full sealed with Anti-corrosion enclosure
- 15" LCD with full flat Resistive touch
- IP67 M12 metal connectors
- Special inspection of 100% waterproof guarantee
- CE, FCC, VCCI Class B certified
- Optional Mini-PCle WLAN with external antenna
- Optional PCAP touch with IP69K true tested
- Optional IP67 solution



Main System

CPU	FCBGA1023 3rd Generation Intel® Core i7/i5/i3/Celeron processor (17W max.)
Chipset	Intel® HM65
Graphics	Intel® integrated HD Graphics 4000
Memory	Two 1600 MHz DDR3 SODIMM socket support dual Channel, non-ECC, up to 16 GB

LCD Panel

Size	15" 4:3
Resolution	1024 x 768 (XGA)
Color numbers	16.7M colors (RGB 6bit + HiFRC)
Viewing angle	160 (H) / 160 (V)
Contrast	600:1
Brightness	400 nits

Touch Panel

Type	Full Flat Resistive touch, 5-wire
Light transmission	80±5%
Hardness	4H
Life time	35 million times

Storage & Expansion

HDD	2.5" SATA HDD drive bay x 1
Expansion slot	Mini PCIe x 2

I/O & Power & Control Keys

USB	1 x M12 8pin for USB 1/2 1 x M12 8pin for USB 3/4
COM	1 x M12 8pin for COM 1/RS-232 1 x M12 8pin for COM 2/RS-232
LAN	1 x M12 8pin for LAN 1
Power input	1 x M12 5pin DC power connector, DC7V~32V
Power adaptor	AC 90 ~ 264V / 47 ~ 63 Hz / DC output 12V, IP67, 60W
Power consumption	45.838 W (MAX. Loading without adaptor)
Control keys	Rear bottom: Power on/off


Mechanical & Environmental

Housing	Stainless steel (SUS304), chassis type
IP rating	IP66 whole set (include the I/O connectors & control keys)
Cooling	Fanless
Dimension	395 x 309.5 x 58 mm (W x H x D, not include I/O connectors)
Weight (net)	8.4 Kg (net)
Temperature	Operating – 0°C~40°C (air flow cooling) Storage – -20°C~60°C
Humidity	Operating & storage – 10%~90%, non-condensing
Regulatory	FCC, CE (EMC), VCCI Class B

Ordering Information

WTP-9A66-15 (i5)	15" FANLESS	Core i5-3317U/2G/320G/Full flat R-Touch
WTP-9A66-15 (i7)	15" FANLESS	Core i7-3517U/2G/320G/Full flat R-Touch

Outline Drawing




Options

Wireless or Wireless + BT kit (2 ant)
M12 to 1x COM cable (cable length is 2 meters)
M12 to 1x USB cable (1 USB Port) (cable length is 2 meters)
M12 to 2x USB cable (2 USB Port) (cable length is 2 meters)
M12 to 1x LAN cable (cable length is 2 meters)
SSD
Wall mount / table mount bracket
2 External LAN (USB x2, LAN x2, COM x1)
TPM
IP69K
IP67

Customization

1000 nits high brightness LCD
Sunlight readable optical bonding
Anti UV and 7H coating
LCD Auto dimming
LCD Super dimming (Low brightness)
Level 6 adaptor



- 1 Giga LAN
- 2 USB 1/2
- 3 USB 3/4
- 4 COM x 2
- 5 DC-in
- 6 Power on/off



Thermal solution and exclusive i-cooling system design