

# FM10MG-V

10.4" Android Vehicle Computers with Genio 510 A78 + A55 CPU



## KEY FEATURES

- Features an ARM Genio 510 processor with 2 x Cortex-A78 cores and 4 x Cortex-A55 cores, both operating at 2.0GHz, providing exceptional performance and efficient multitasking.
- Features a 10.4-inch panel with a resolution of 1024 x 768, equipped with a PCAP touchscreen for responsive and intuitive user interaction.
- The device has an IP65 rating, making it waterproof and dustproof, ensuring reliable performance in harsh conditions.
- Supports a wide power input range of 10-60V DC with ignition control for flexible installation and operation.
- Designed to operate over a wide temperature range, ensuring reliable performance in various environmental conditions.
- Supports VESA mounting, allowing for versatile installation options and easy integration into different setups.
- Features replaceable front and rear modules for enhanced convenience and cost-effectiveness.

## INTRODUCTION

Winmate FM-V Series Android Vehicle Mounted Computer (VMC) delivers robust performance and versatility for industrial and automotive applications. Available in sizes from 7" to 14", it features powerful processor options, including ARM A78 and A55 cores, ARM A53 Quad Core, and Qualcomm® Snapdragon™ 660. Designed with IP65-rated waterproof and dustproof protection, wide 10-60V DC power input with ignition, and reliable operation in extreme temperatures, the FM-V Series ensures durability and efficiency. With VESA mount support, it is perfect for fleet management, warehouse operations, and forklift-mounted applications.

## SPECIFICATIONS

### Display


Resolution	1024x768	Size	10.4 inches
Contrast Ratio	1200:1	Panel Brightness	400 nits 800 nits(Optional)
View Angles	88,88,88,88	Type	Projected Capacitive Multi Touch
Touch Mode	Support Hand, Stylus, Glove Mode		

### System Specification

Processor	ARM Genio 510 2 x A78 2.0GHz + 4 x A55 2.0GHz	Memory	4GB LPDDR4
Storage	Onboard 64 GB	Operating System	Android 13 Linux Yocto 5.10.104 with QT 5.15 (Optional) Linux Ubuntu 22.04 (Optional)
WLAN	Support	BT	Support
WWAN	4G/LTE (Optional)	GNSS	GPS/GLONASS (Optional)

<b>Sensors</b>	G-Sensor, Light Sensor, Temp Sensor		
<b>Camera</b>			
<b>Front Camera</b>	2MP Camera		
<b>Mechanical</b>			
<b>Dimension</b>	268 x 214 x 51 mm	<b>Weight</b>	2.4 kg
<b>Mounting</b>	VESA Mount	<b>Docking Housing</b>	nan
<b>IO Ports</b>			
<b>USB Port</b>	1 x USB 2.0 Type C (OTG) 1 x USB 2.0 Port	<b>Serial Port</b>	2 x RS232/422/485 (Default RS232)
<b>SD Card Slot</b>	1 x Micro SD Card Slot	<b>SIM Card Slot</b>	1 x Dual-Nano SIM Card Slot
<b>Audio</b>	1 x Audio(Mic in & Line Out) either one with DIDO (Optional)	<b>LAN</b>	1 x Gigabit LAN port PSE (IEEE 802.3at 30W) (Optional)
<b>Indicator</b>	5 x LED Indicator (Wi-Fi, BT, UPS battery, Screen Blanking, Heater)	<b>DIDO</b>	1 x DIDO (2XDI ; 2XDO) either one with Audio (Optional)
<b>CANBUS</b>	1 x CANBus (Optional)		
<b>Environment</b>			
<b>Operating Humidity</b>	5% to 95% RH, Non-Condensing	<b>Operating Temperature</b>	-30°C to 60°C
<b>Storage Temperature</b>	-30°C to 60°C	<b>Shock</b>	MIL-STD-810H Method 516.8 Procedure I
<b>Vibration</b>	MIL-STD-810H Method 514.8 Procedure I	<b>IP rating</b>	IP65
<b>Impact</b>	Support EN62262 IK07 Rating	<b>ESD</b>	Compliant with EN 61000-4-2, Enhanced ESD to ±8kV Direct & ±15kV Air
<b>Certification</b>			
<b>Certification</b>	CE, FCC		
<b>Control</b>			
<b>Button</b>	1 x Power Button, 6 x Function Button (Programmable Function Key Configured by Winset)		
<b>Power</b>			
<b>Battery</b>	400mAh UPS Battery for 20 minutes backup (Optional)	<b>Power Rating</b>	10V~60V with ignition control
<b>Consumption</b>	35W (Typical)		
<b>Security Function</b>			
<b>SOTI MobiControl</b>	SOTI MobiControl Compliance		
<b>Accessory</b>			
<b>Accessory</b>	1.8M Power Cable with Fuse Kit 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Quick Start Guide	<b>Optional Accessory</b>	5M Power Cable with Fuse Kit/Stylus Kit + Screw 1.8M RS232 Cable 2M IP65 LAN Cable GPS & LTE 5M Combo Antenna (VM9C) GPS & LTE Magnetic Combo Antenna (VM10S) GPS Antenna WWAN Antenna 2M Waterproof USB Type-A to A Cable Cable Clamp Kit COM Port + CANBus Cable COM Port + DIDO Cable

## DIMENSIONS UNIT:MM



## NOTE

1. Total usable memory will be less dependent upon actual system configuration.
2. DIDO and audio are mutually exclusive.
3. The heater is a customized feature available by request.
4. SOTI is available upon request.
5. Length measurements do not include protrusions. Weight varies with options.
6. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
7. Accessories may vary depending on your configuration.
8. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
9. This is a simplified drawing and some components are not marked in detail.
10. The UPS battery is only expected to use for backup under low system loading and without I/O function.
11. COM port can supply 5V power via the 9th pin.