Aluminum Portable Workstation

15" LCD monitor, support SBC+ PBP, offer 11 expansion slots



- All Aluminum Construction
- Offer 11 slots expansion capability
- High brightness 15" TFT LCD display
- SBC with Backplane




87 Keys membrane keyboard

2 USB ports

Introduction

The EMP 350 is a robust lunchbox computer built using heavy duty metal to provide tough, go-anywhere unit ideally suitable for harsh/severe environments and mission critical applications. With passive backplane board configurations to choose from, the 11 full length expansion slots of the EMP 350 can be freely configured with other uniquely designed expansions cards for most applications.

Also designed for harsh environment operations, the LCD screen of the EMP 350 is guarded with a specially treated anti-glare tempered glass for added protection. Every EMP 350 comes equipped with dual system cooling side fans and easy access to its expansion ports for immediate system upgrade or maintenance. Functional practicality combined with the simple and polished design, the EMP 350 with its extra-rugged construction to sustain bumps and impacted blows is the most cost-effective, durable and efficient portable solution for your mission critical applications.



www.ipc2u.ru www.ipc2u.de www.sovio.com Date: 01/07/2016

Specification

Model No	EMP350-15	
Motherboard	Support SBC+PBP	
Slots	Offer 11 expansion slots	
Drive bay	1 x 5.25" Slim Combo, 1 x 3.5" Slim FDD 2 x 3.5" hidden	
Display	Size	15" TFT LCD monitor
	Brightness	250 nits
	Resolution	1024 x 768
	Protection	Anti-reflection tempered strengthen glass
VGA	Analog-to-digital conversion board	
Keyboard/ Mouse	NB 87 keys, multi-languages/touchpad, RJ45 connector	
Case Size	411mm x 305mm x 226mm (16.18" x 12.01" x 8.9")	
Power Supply	1U, 400W (Auto Sensing Active PFC)	
SKD Weight	12 kgs (26.46 lbs)	
	Built-in amplified speakers	
Speaker	Amplified board output: 2 x 6 Watt Stereo	
	Dual Speaker output: 2 Watt	
Carrying Case	Padded carrying case with wheels	

Internal View of EMP 350



Ordering Information

• EMP 350

15" LCD, 11 slots, A/D board, 87 K/B with Touchpad, 1x5.25"/3x3.5" Drive bays, 400W PSU, Carrying bag

Mechanical/Environmental

Operating Temp.	0°C-50°C
Relative Humidity	20-80% (non-condensing)
Operating Shock	15g
Operating Vibration	10-100Hz 1.25g
Approval	CE, FCC

