

PDSB 125

Fanless Digital Signage Player Powered by
Intel® Atom™ Dual Core D525 Support Full HD Video Playback



Product Overview

PDSB 125 is an Intel® Atom™ Dual Core D525 based digital signage player pre-loaded with user-friendly digital signage software, the PowerDigiS, targeting for entry-level digital signage applications. PDSB 125 is enclosed in a compact chassis with low power consumption and can be easily integrated to display device such as LCD TV or PDP at site installation. PDSB 125 is capable to layout display into multiple rectangle zones and play rich multi-media contents on each zone in accordance with user defined schedule table. This makes the PDSB 125 work perfect for increasing digital signage applications within retail outlets, department store, entertainment venues, restaurants, hotels, bus/train station, schools/universities and hospitals for dynamic message delivering, advertising, or brand promotion.

Presentation Design Tool

The presentation design tool is one of the most valuable parts of the PowerDigiS software. It helps digital signage content creator on intuitive operations to ease the output of presentation to the player. The tool provides quick screen layout design function. The screen layout can be saved as template for reuse. The tool provides an easy drag and drop method to organize contents in playlist and associate playlist to each zones in the screen layout. The tool provides handy preview function for individual content files and final presentation. The presentation design tool also integrates easy upload function to publish presentation design to removable media, central management server, or player.

User's Benefits

- Seamless hardware and software integration for operation reliability
- Flexible display configuration
- Presentation design is simple and intuitive
- Presentation publish and scheduling is easy
- Presentation content support is rich and versatile
- Self-contained device for easy deployment

Software Specifications

Content Source

- Local disk or network server

Video File Format

- MPEG 1/2/4, AVI, WMV, DivX, XVID, VOB, MOV VC-1, H.264, rm, rmvb

Flash File Format

- SWF, FLV

Picture File Format

- JPG, BMP, PNG, ICO, ICP, GIF, TIFF, WMF

Sound Format

- MIDI, MPEG-1-Audio LayerII (MP2), mp3, SND,M4A,AAC,wav, wma, ogg, ra

Web/Data

- Web URL
- Text files
- RSS news feed

Screen Support

- Single display, or two clone displays
- Portrait or landscape orientation
- Presentation can be segmented to different screen layouts
- Up to 9 display zones in each screen layout

Playing Effect

- Scrolling text and emergency message
- Image transition effect
- Multiple languages

Content Throughput

- Up to 2x HD video zones, or 1 x Full HD video zone, or 1 x shockwave flash zone
- Multiple pictures and scrolling text zones

Management Function

- Web-based management with password access control
- Multilingual management interface
- Presentation management
- Presentation scheduling
- System event log
- Presentation playing log
- Presentation play/ pause/ stop control function
- System reboot, shutdown, firmware upgrade

Presentation Design

- Presentation layout and playlist editing function
- Presentation and content file preview function
- Presentation publish function

Operating System

- Ubuntu Linux

Hardware Specifications

Storage Device

- 160GB SATA HDD

I/O Interface

- 1 x VGA; 1 x HDMI
- 1 x Audio Line-out
- 4 x USB
- 1 x RJ45 with LEDs for 10/100/1000Mbps Ethernet

Power Supply

- 1 x External 60W AC/ DC adapter
Input: 100~240VAC
Output: +12VDC

Dimensions

- 250.5mm (W) x 195mm (D) x 40mm (H) (9.9" x 7.7" x 1.6")

Environment

- Operating temperature: ambient with air flow from 0°C to 40°C
- Storage temperature: -40°C to 80°C
- Humidity: 10% to 90% (non-condensing)

Certification

- CE approval
- FCC Class A

Ordering Information

- **PDSB 125 (P/N: 10B00B12500X0)**