



RMDDU



The RMDDU is a rugged 2U rackmount drawer with dual-screen LCD monitors at 17.3", 19", or 23". The displays fold together and rotate close into the drawer for slide in storage.

It is an ideal match in military transit case applications and command & control centers. The compact 2U rackmount display drawer uses a secure all-aluminum monitor mounting and stabilization design necessary for robust government & defense, communications and industrial automation applications. It is also designed for server room applications.



RMDDU Technical Specifications

Model	RMDDU 17A	RMDDU 17"	RMDDU 19"	RMDDU 23"
Dimensions/Weight	3.46" x 17.76" x 25.89" (H x W x D) / 48 Lbs 88mm x 451.2mm x 657.6mm (H x W x D) / 21 kg		3.46" x 17.76" x 25.89" (H x W x D) / 53 Lbs 88mm x 451.2mm x 657.6mm (H x W x D) / 24 kg	3.43" x 19.60" x 32.23" (H x W x D) / 60 Lbs 87.3mm x 497.8mm x 818.6mm (H x W x D) / 27 kg
Display	2x 17.3", 16:9 Display 1920x1080		2x 19", 5:4 Display 1280x1024	2x 23", 16:9 Display 1920x1080
Display Deployment	Displays rotate up from stowed position, rotate & open via butterfly action and slide to center the two displays on the operator			
Display Tilt	Displays tilt ~10° from vertical for optimal operator positioning			
Signal Inputs	Analog VGA, DVI-D, HD-SDI, S Video-In for each display		Analog VGA, DVI-D, HDMI Displayport for each display	
Display Adjustment	Individual brightness, contrast, color temperature adjustments			
USB Pass Through	2x USB pass through inputs on the front panel		Internal USB 2.0 hub with 2x inputs on the front panel and a single USB 2.0 on the rear	
Keyboard	101-key pull out backlit keyboard			
Pointing Device	Resistive touchpad			
Input Power	18 - 36VDC		115/230 VAC, 50/60Hz, 100W Max	
Internal	Teflon coated wires		5-minute backup, internal battery, switch over indicator	

Specs subject to change. Customizations available through sales rep.

Environmental Specifications

Temperature: MIL-STD-810E (501.4, 502.4)	Operating: 0 ~ 50°C Non-Operating: -40 ~ 70°C
Humidity: MIL-STD-810E (507.2)	Relative Humidity: 5% to 95% operating, non-condensing
Altitude: MIL-STD-810E (500.3)	Operating: 15,000 ft (4571.8 m) Non-Operating: 40,000 ft (12,192 m)
Vibration: MIL-STD-810E (514.4)	Operating: 10 to 500 Hz 1.04 g (RMS)
Shock: MIL-STD-810E (516.4)	Operating: 15 G, 8 ms 1/2 sine Non-Operating: 40 G, 8 ms 1/2 sine Drop: 4" stand alone, 39" transit drop in transit case
Compliance	CE, FCC, UL, CCC, ROHS

Acme Portable Machines, Inc.

Contact us to request a quote today!



Headquarters - USA
ACME Portable Machines, Inc
1330 Mountain View Circle
Azusa, CA 91702, USA
Tel: +1 626.610.1888
Fax: +1 626.610.1881

Germany
ACME Portable Computer GmbH
Benzstraße 15
76185 Karlsruhe, Germany
Tel: +49.721.570.4530
Fax: +49.721.570.45329

Taiwan
ACME Portable Corp.
5F, No 25, Wuquan 3rd Road,
Wugu Dist., New Taipei City 248, Taiwan R.O.C
Tel: +886.2.2298.3636
Fax: +886.2.2298.3737

www.ipc2u.ru www.ipc2u.de www.sovio.com Date: 01/07/2016