

SMK580

The Multiple systems solution 8 ports



Specification :

Model No	SMK 580-15	SMK 580-17
KVM switch	8 ports KVM switch. Daisy chain level up to 8 Levels. PC connection up to 120 sets	
Weight	16kgs	16.5kgs
Dimension	442.4x44.5x590 mm (W x H x D)	
Power Supply	AC 110/220V Auto Switch	
Construction	Heavy-duty steel	
Keyboard	Membrane 105 keys with touchpad	
Protection	Tempered glass protection to the LCD screen	
Operation Temperature	0-50° C (32-122°F)	
Approval	CE, FCC, UL, CCC	

Display

Diagonal	15" (381mm),	17" (431.8mm)
LCD Resolution	1024 x 768	1280 x 1024
Brightness	250 nits	300 nits
Viewing angle	120/120	160/160
Contrast Ratio	350:1	450:1
Backlight MTBF	50,000 hours under 25±5	
Frame Rate	60Hz	

KVM Switch

Operating System	Win 95/98/98SE/2000/ME/XP, DOS, Win 3.X, WinNT, Netware, SCO Unix, HP Unix, Linux
Hot Plug	Add PCs or Remove Connected PCs for Maintenance without powering down the KVM switch for PCs
Auto Scan Mode	5s - 99s



Front Push Buttons to select your need PCs

Features :

Meets EIA310c & IEC-3 specifications

One set built-in Keyboard, touch pad, monitor and 8 ports KVM switch

Easy PC selection via Front push buttons,

Hot keys, On Screen Display

Support eight characters password protection and search PC server name.

Auto scan mode for monitoring PCs

Standard VGA, keyboard, mouse Cable

