

# SMK590 *The Multiple systems solution 16 ports*

## Specification :

Model No	SMK 590-15	SMK 590-17
KVM switch	16 ports KVM switch. Daisy chain level up to 8 Levels. PC connection up to 128 sets	
Weight	17kgs	17.5kgs
Dimension	442.4x44.5x625 mm (W x H x D)	
Power Supply	AC 110/220V Auto Switch	
Construction	Heavy-duty steel	
Keyboard	Membrane 105 keys with touchpad	
Protection	Tempered glass protection to the LCD screen	
Operation Temperature	0-50° C (32-122°F)	
Approval	CE, FCC, UL, CCC	

### Display

	SMK 590-15	SMK 590-17
Diagonal	15" (381mm),	17" (431.8mm)
LCD Resolution	1024 x 768	1280 x 1024
Brightness	250 nits	300 nits
Viewing angle	120/120	160/160
Contrast Ratio	350:1	450:1
Backlight MTBF	50,000 hours under 25±5	
Frame Rate	60Hz	

### KVM Switch

Operating System	Win 95/98/98SE/2000/ME/XP, DOS, Win 3.X, WinNT, Netware, SCO Unix, HP Unix, Linux
Hot Plug	Add PCs or Remove Connected PCs for Maintenance without powering down the KVM switch for PCs
Auto Scan Mode	5s - 99s



Front Push Buttons to select your need PCs

## Features :

Meets EIA310c & IEC-3 specifications

One set built-in Keyboard, touch pad, monitor and 16 ports KVM switch

Easy PC selection via Front push buttons,

Hot keys, On Screen Display

Support eight characters password protection and search PC server name.

Auto scan mode for monitoring PCs

D-Sub 15 pin to VGA, keyboard, mouse cable

