

## Installation Options

ATEN LCD KVM Switches/LCD Consoles allow you to choose from a host of optional rack mount kits to meet your needs, including the Single Person Easy Installation Rack Mount Kit, which streamlines the rack mounting process. Normal rack mounting procedures call for at least two people to rack mount an LCD KVM switch/LCD Console. The Single Person Easy Installation Rack Mount Kit enables one person to rack mount an LCD KVM Switch. In just a matter of minutes, your new LCD KVM Switch/LCD Console can go from the box to the rack.

### Single Person Installation

The following illustrations demonstrate just how easy it is to install your LCD KVM Switch with the Easy Installation Rack Mount Kit.



1. Secure the side rails to the rack.



2. Slide the LCD KVM Switch onto the rails and secure it to the rack.



3. Now slide it out and you are ready to work.

### Standard Installation Rack Mount Kit

Standard Installation - Short (Standard)



Standard Installation - Long (2X-010G)



Standard Installation - Long (2X-023G)



### Easy Installation Rack Mount Kit

Easy Installation - Short (2X-011G)



Easy Installation - Long (2X-012G)



Easy Installation - Short (2X-024G)



Easy Installation - Long (2X-025G)



## Rack Mount Kit

Model No.	Bracket Type	Depth (cm)
CL1000N, CL1308N, CL1316N	Standard Installation - Short (Standard)	52 - 85
	Standard Installation - Long (2X-023G)	70 - 105
	Easy Installation - Short (2X-024G)	57 - 70
	Easy Installation - Long (2X-025G)	68 - 105
CL3000N, CL5800N, CL6700N, CL6700MW, CL5708N, CL5716N, CL5808N, CL5816N	Standard Installation - Short (Standard)	52 - 85
	Standard Installation - Long (2X-010G)	70 - 105
	Easy Installation - Short (2X-011G)	57 - 70
	Easy Installation - Long (2X-012G)	68 - 105
CL1008M, CL1016M, CL5708M, CL5716M	Standard Installation - Short (Standard)	42 - 82
	Standard Installation - Long (2X-010G)	68 - 105
	Easy Installation - Short (2X-011G)	52 - 70
	Easy Installation - Long (2X-012G)	68 - 105
CL1000M	Standard Installation - Short (Standard)	42 - 72
	Standard Installation - Long (2X-010G)	68 - 100
	Easy Installation - Short (2X-011G)	42 - 70
	Easy Installation - Long (2X-012G)	68 - 105
KL1508AN, KL1516AN, KL1508AiN, KL1516AiN	Standard Installation - Short (Standard)	42 - 77
	Standard Installation - Long (2X-010G)	68 - 105
	Easy Installation - Short (2X-011G)	63 - 70
	Easy Installation - Long (2X-012G)	74 - 105
KL1508AM, KL1516AM, KL1508AiM, KL1516AiM, KL9108M, KL9116M	Standard Installation - Short (Standard)	42 - 77
	Standard Installation - Long (2X-010G)	68 - 105
	Easy Installation - Short (2X-011G)	57 - 70
	Easy Installation - Long (2X-012G)	68 - 105

