

**DP-665**  
**24V/2.5A, 5V/0.5A Power supply**



**Model: DP-665**

## Introduction

DP-665 is a 65 watts, universal input switching mode power supply.

It is with 24V/5V output options. DP-665 is intended for power device like motor or solenoid application. Build in +5V 3T-regulator for DP-665 is for if there is a logical control circuit.

## Features

- Input voltage : 85 VAC ~ 270 VAC
- Input frequency : 47 Hz ~ 63 Hz
- Inrush current (Cold start):  
less than 30A at 115 VAC  
less than 60A at 230 VAC
- DC Outputs:  
+24 V/2.5 A  
+5 V/0.5 A
- Efficiency : higher than 70% at rated load and 115 VAC
- Holdup time : 16ms at rated load and 115 VAC
- Over voltage protection : hiccup mode
- Short circuit protection : latch off
- Over voltage protection : latch off

- Operating temperature : 0 ~ 50 °C
- Cooling : free air convection
- Storage temperature : -40 °C ~ +85 °C
- Dimensions : 210 mm x 42 mm x 116 mm



**I-8000 Series with DP-665**

## Ordering Information

DP-665	24V/2.5A 5V/0.5A Power Supply
--------	-------------------------------

[TOP](#) | [HOME](#)