



Relay Output
Features
7 Form A Power Relay
■ 4 kV ESD Protection
Power On Value Setting
Safe Value Setting
RoHS Compliance
Dual Watchdog
■ Wide Range of Operating Temperature: -25 °C ~ +75 °C
CE FC KHS Z

#### ■ Introduction \_

I-7067 features 7-channel Form A power relay outputs. I-7067D also has 7 LED indicators for power relay outputs. There are options for power on value and safe value for your consideration. All DO channels have 4KV ESD protection.

### Applications \_\_

Building Automation, Factory Automation, Machine Automation, Remote Maintenance, Remote diagnosis, Testing Equipment.


# I/O Specifications \_\_\_\_\_

Relay Output		
Output Channels		7
Relay Type		Form A relay SPST (N.O.)
Contact Rating	AC	0.5 A @ 120 Vac
Contact Rating	DC	1 A @ 24 Vpc
Operating Time (Max.)		5 ms
Release Time (Min.)		2 ms
Surge Strength		1500 Vac
Life Time	Mechanical	20 x 10^6 OPS
Life Time	Electrical	100 x 10^3 Full Load

## ■ System Specifications —

Interface		
Interface		RS-485
Format		N, 8, 1
Baud Rate		1200 ~ 115200 bps
LED Display  Power		1 LED as Power/Communication indicator
		7 LEDs as relay output indicators
		(for I-7067D)
Input Voltage Range		+10 Vpc ~ +30 Vpc
Power	I-7067	1.5 W
Consumption	I-7067D	2.2 W
Environment		
Operating temperature Storage temperature Humidity		-25 °C ~ +75 °C
		-40 °C ~ +85 °C
		5 ~ 95% RH, non-condensing
Dimensions		72 mm x 122 mm x 35 mm (W x L x H)

### ■ Internal I/O Structure \_




### 

Terminal No.	Pin Assignment	20	11	Terminal No.	Pin Assignment
01	RL6 NO	//	*****	20	RL5 COM
02	RL6 COM		<b>-</b>	19	RL5 NO
03	RL7 NO	102	CON	18	RL4 COM
04	RL7 COM	1-70	067	17	RL4 NO
05		9 1-70	167D 🥞	16	RL3 COM
06	INIT*			15	RL3 NO
07	(Y)DATA+		/	14	RL2 COM
08	(G)DATA-	\\	-	13	RL2 NO
09	(R)+Vs	99999	999999	12	RL1 COM
10	(B)GND	ļ 01	10	11	RL1 NO

#### ■ Wire Connection —

Relay On	Relay Off
AC/DC C RLx NO	CODE X D RLx NO RLx COM

## ■ Dimensions (Unit: mm) \_



# ✓ Ordering Information \_\_\_\_\_

I-7067 CR	7-channel Relay Output Module (RoHS)
I-7067D CR	I-7067 with LED Display (RoHS)

#### Related Products \_\_\_\_\_

Converters	USB, RS-232, Fiber Optical to RS-485 Converters and Repeaters	
Power Supply	24 Vpc Power Supply	
Relay Module	External Polay Modules for L-7000 DO Module	

Learning Kit	Starter Learning Kit
Application Books	Application Books Designed with Our Products
Data Logger Software	User Friendly Data Logger Software (free)