


CP-114EL/EL-I

4-port RS-232/422/485 PCI Express boards with optional 2 kV isolation



- > PCI Express x1 compliant
- > 921.6 kbps maximum baudrate for super fast data transmission
- > 128-byte FIFO and on-chip H/W, S/W flow control
- > Low profile form factor fits small-sized PCs
- > Drivers provided for a broad selection of operating systems, including the latest Windows and Linux
- > 15 kV ESD protection on the board



12

Multiport Serial Boards > CP-114EL/EL-I

Overview

The CP-114EL and CP-114EL-I are smart, 4-port PCI Express boards designed for POS and ATM applications. The boards are a top choice of industrial automation engineers and system integrators, and support many different operating systems, including Windows and Linux. In

addition, each of the boards' 4 RS-232/422/485 serial ports supports a super fast 921.6 kbps baudrate. The CP-114EL and CP-114EL-I provide full modem control signals to ensure compatibility with a wide range of serial peripherals, and their PCI Express "x1" classification allows the boards to be installed in any PCI Express slot.

Smaller Form Factor

The CP-114EL and CP-114EL-I are low profile boards that are compatible with any PCI Express slot. The boards require only a 3.3

VDC power supply, which means that the boards fit any host computer, ranging from shoebox to standard-sized PCs.

Drivers Provided for Windows, Linux, and Unix

Moxa continues to support a wide variety of operating systems, and the CP-114EL/EL-I boards are no exception. Reliable Windows COM

and Linux TTY drivers are provided for all Moxa boards, and other operating systems, such as WEPOS, are also supported for embedded integration.

Specifications

Hardware

Comm. Controller: 16C550C compatible

Bus: PCI Express x1

Connector: DB44 female

Serial Interface

Number of Ports: 4

Serial Standards: RS-232/422/485

Max. No. of Boards per PC: 4

Serial Line Protection

ESD Protection: 15 kV on the board

Electrical Isolation: 2 kV (CP-114EL-I only)

Performance

Baudrate: 50 bps to 921.6 kbps

Serial Communication Parameters

Data Bits: 5, 6, 7, 8

Stop Bits: 1, 1.5, 2

Parity: None, Even, Odd, Space, Mark

Flow Control: RTS/CTS, XON/XOFF

Serial Signals

RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

RS-422: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-4w: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-2w: Data+(B), Data-(A), GND

Operating Systems

Windows Real COM Drivers: Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), DOS

Fixed TTY Drivers: QNX 6, SCO OpenServer, UnixWare 7, Solaris 10

Linux Real TTY Drivers: Linux 2.4.x, 2.6.x, 3.x

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions:

CP-114EL: 67.21 x 103 mm (2.69 x 4.06 in)

CP-114EL-I: 67.21 x 135 mm (2.69 x 5.31 in)

Environmental Limits

Operating Temperature: 0 to 55°C (32 to 131°F)

Storage Temperature: -20 to 85°C (-4 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Altitude: Up to 2000 m

Note: Please contact Moxa if you require products guaranteed to function properly at higher altitudes.

Standards and Certifications

EMC: CE, FCC

EMI: EN 55022, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class B

EMS: EN 55024, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 (DIPS)

Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 684,289 hrs

Database: Telcordia (Bellcore), GB

Power Requirements

Power Consumption:

CP-114EL: 835 mA @ 3.3 V

CP-114EL-I: 1170 mA @ 3.3 V


Warranty

Warranty Period: 5 years


Details: See www.moxa.com/warranty

Dimensions

CP-114EL



CP-114EL-I



Unit: mm (inch)

Ordering Information

Available Models

CP-114EL: 4-port RS-232/422/485 low profile PCI Express x1 serial board

CP-114EL-I: 4-port RS-232/422/485 low profile PCI Express x1 serial board with electrical isolation

CP-114EL-DB9M: 4-port RS-232/422/485 low profile PCI Express x1 serial board (includes DB9 male cable)

CP-114EL-DB25M: 4-port RS-232/422/485 low profile PCI Express x1 serial board (includes DB25 male cable)

CP-114EL-I-DB9M: 4-port RS-232/422/485 low profile PCI Express x1 serial board with electrical isolation (includes DB9 male cable)

CP-114EL-I-DB25M: 4-port RS-232/422/485 low profile PCI Express x1 serial board with electrical isolation (includes DB25 male cable)

Connection Options (can be purchased separately)

Package Checklist

- 1 CP-114EL or CP-114EL-I board
- Standard bracket and low profile bracket
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card


CBL-M44M9x4-50

DB44 male to DB9 male x 4 (50 cm cable)



PIN	RS-232	RS-422	RS-485-4w	RS-485-2w
1	DCD	TxD-(A)	TxD-(A)	-
2	RxD	TxD+(B)	TxD+(B)	-
3	TxD	RxD+(B)	RxD+(B)	Data+(B)
4	DTR	RxD-(A)	RxD-(A)	Data-(A)
5	GND	GND	GND	GND
6	DSR	-	-	-
7	RTS	-	-	-
8	CTS	-	-	-
9	-	-	-	-

DB9 male



CBL-M44M25x4-50

DB44 male to DB25 male x 4 (50 cm cable)



PIN	RS-232	RS-422	RS-485-4w	RS-485-2w
2	TxD	RxD+(B)	RxD+(B)	Data+(B)
3	RxD	TxD+(B)	TxD+(B)	-
4	RTS	-	-	-
5	CTS	-	-	-
6	DSR	-	-	-
7	GND	GND	GND	GND
8	DCD	TxD-(A)	TxD-(A)	-
20	DTR	RxD-(A)	RxD-(A)	Data-(A)
22	-	-	-	-

DB25 male

